



50W

Features

Aluminum alloy with high thermal conductivity, 3.5mm lead free toughened glass, durable and completely corrosion resistance.

Use 1PCS integrated high - power LED (COB).

IP rating is up to IP65.

High utilization of power, PF>0.95

Compared with traditional ones, energy - saving percentage: 60%

Insulation rate, Class 1.

Service life over 50000 hours

Follow RoHS and CE certified.

Technical Parameters

Model No.	DGL-HB50-50W
Input Voltage	85-265V AC, 50-60Hz
LED Q'ty	1pcs*50W
LED Efficiency	80-90lm/W
Initial Lumens	>4500lm (cool white) >4250lm (natural white) >4000lm (warm white)
Power Factor	>0.95
Color	cool white/ natural white/ warm white
Beam Angle	120 degrees
Finished Color	Black/ lamp holder, Silver/ reflector
Housing Material	Aluminum
IP Rating	IP65
Life Span	50,000 hrs





Accent Design Concepts

Item No.:HB-003

Certificate	CE, RoHS
-------------	----------

Applications

Apply to workshop, factory building, warehouse, highway toll stations, gas stations, supermarkets, exhibition halls, stadiums and other places of lighting required.



Accent Design Concepts, LLC.

Orlando, Florida 32824

Email: Sales@accentdesignconcepts.com

Website: www.accentdesignconcepts.com

Specifications subject to change w/o notice