

Accent Design Concepts

Item No.:HB-004



Details

1) Heat sink is designed to be integrated	ed with housing, which improves
heat dissipation condition and reduces junction temperature.	

- 2) Anodized heat sink, housing surface is coated with anti-static powder, and antirusted treated, the entire unit is with IP65 rated.
- 3) Imported high lumen LED chip, the SMD LED source is assembled by patented packing knowledge, single SMD LED is with 10~100W, the lumen output is up to 100lm/W.
- 4) LED driver with efficient as high as 91%, high accuracy and long lifespan.
- 5) Wide AC input 85V~265Vac/47~63Hz, universally available.
- 6) International EMC Passed

Application

Workshop, toll gate, exhibition centre, gymnasium, ware house, gas station, parking area etc.

Voltage	85~265V AC
	WW: 3,900lm
Lumens	NW: 6,000lm
	CW: 7,000lm



Accent Design Concepts

Item No.:HB-004

Average Illuminance	Height of 4-meter: 120 lux
	Height of 6-meter: 70 lux
	Height of 8-meter: 35 lux
Dimension	465L x 465W x 542H
	mm
Beam Angle	40
Weight	8.0kg
LED Type	SMD Bridgelux
Power Consumption	200.0W
	More options for 30,
Note	40, 50, 70, 80, 100,
	120W