



ORDER MATRIX | Example: G4011-B

A	B	C	D	E
A	Series			
G4011-B	1-Lamp			
G4012-B	2-Lamp			
G4013-B	3-Lamp			
G4014-B	4-Lamp			
G4014-B-S	4-Lamp			
B	Input Voltage			
	120V			
277	277V			
U	120V-277V			
C	LED Available			
Cree	Cree			
Citizen	Citizen			
Epistar	Epistar			
Seoul	Seoul			
Osram	Osram			
D	Color Temperature			
27K	2700K			
30K	3000K			
35K	3500K			
41K	4100K			
E	Optics			
12°	12° spot			
24°	24° narrow flood			
36°	36° flood			

Description

- Easy Installation and maintenance
- All parts and components accessible from below the ceiling
- Lamp holders are adjustable 360° horizontal and 30° vertical for spot lighting in multiple directions
- Actual adjustment may vary depending on the lamp beam spread

Housing

- The inner trim is constructed of 22GA steel
- Finish can be black, white or silver
- Special finish please confirm with factory
- Internal wire bundles are locked and covered with a glass sleeve
- Junction box can be accessible from below the ceiling with a plate

Mounting Frame

- Can be accommodate a 1/2" to 1 1/4" ceiling thickness
- Channel bracket allow up to 5" vertical adjustable
- Universal mounting brackets included
- Compatible with C-channel, flat bar, and EMT
- C-channel are recommended for T-bar ceilings
- Bar hangers must be ordered separately

Flanged Trim

- Extruded trim frame includes torsion springs for convenient installations or removal from the housing

Trimless

- Optional mud frame available for trimless mounting
- The perforated mesh frame provided adheres to joint compound for seamless and trimless mounting

LED Light Engine

- 2700K-4100K
- CRI>80%
- LED mounted to die-cast/extruded aluminum heat sink
- 50000 hours average rated life at 70% lumen

Electrical System

- 120-277V input
- Class 2 power supply
- Over voltage, over current and short circuit protection
- Auto recovery
- 10% dimmable is available 120V only
- 10/15/17.8/20W each lamp
- LM from 650-950 each lamp

Lamp Q'ty (PCS)	Wattage (W)	Lumen (LM)	Color Temperature (K)
1 lamp	20W	950LM	2700K-4100K
2 lamps	40W	1900LM	
3 lamps	60W	2850LM	
4 lamps	80W	3800LM	
4 lamps square	80W	3800LM	