

LED FILAMENT BULB

Model	RS-C35-2W	RS-C35-4W	RS-C35T-1W	RS-C35T-2W	RS-A60-4W	RS-A60-6W
Picture	C Series  RS-C35-2W	C Series  RS-C35-4W	C Series  RS-C35T-1W	C Series  RS-C35T-2W	A Series  RS-A60-4W	A Series  RS-A60-6W
Voltage(V)	110V-130V 220V-240V	110V-130V 220V-240V	110V-130V 220V-240V	110V-130V 220V-240V	110V-130V 220V-240V	110V-130V 220V-240V
Wattage(W)	2W	4W	1W	2W	4W	6W
Lumen(lm)	220	440	110	220	440	660
Base	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15
Average Life (hrs.)	30000	30000	30000	30000	30000	30000
CCT	2700k/6000k	2700k/6000k	2700k/6000k	2700k/6000k	2700k/6000k	2700k/6000k
CRI (Ra)	90	90	90	90	90	90
Beam Angle	345°	345°	345°	345°	345°	345°
Model	RS-A60-8W	RS-G45-2W	RS-G45-4W	RS-G80-4W	RS-G80-6W	RS-G80-8W
Picture	A Series  RS-A60-8W	G Series  RS-G45-2W	G Series  RS-G45-4W	G Series  RS-G80-4W	G Series  RS-G80-6W	G Series  RS-G80-8W
Voltage(V)	110V-130V 220V-240V	110V-130V 220V-240V	110V-130V 220V-240V	110V-130V 220V-240V	110V-130V 220V-240V	110V-130V 220V-240V
Wattage(W)	8W	2W	4W	4W	6W	8W
Lumen(lm)	880	220	440	440	660	880
Base	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15
Average Life (hrs.)	30000	30000	30000	30000	30000	30000
CCT	2700k/6000k	2700k/6000k	2700k/6000k	2700k/6000k	2700k/6000k	2700k/6000k
CRI (Ra)	90	90	90	90	90	90
Beam Angle	345°	345°	345°	345°	345°	345°
Model	RS-G95-4W	RS-G95-6W	RS-G95-8W	RS-G125-4W	RS-G125-6W	RS-G125-8W
Picture	G Series  RS-G95-4W	G Series  RS-G95-6W	G Series  RS-G95-8W	G Series  RS-G125-4W	G Series  RS-G125-6W	G Series  RS-G125-8W
Voltage(V)	110V-130V 220V-240V	110V-130V 220V-240V	110V-130V 220V-240V	110V-130V 220V-240V	110V-130V 220V-240V	110V-130V 220V-240V
Wattage(W)	4W	6W	8W	4W	6W	8W
Lumen(lm)	440	660	880	440	660	880
Base	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15
Average Life (hrs.)	30000	30000	30000	30000	30000	30000
CCT	2700k/6000k	2700k/6000k	2700k/6000k	2700k/6000k	2700k/6000k	2700k/6000k
CRI (Ra)	90	90	90	90	90	90
Beam Angle	345°	345°	345°	345°	345°	345°

Model	RS-T45-2W	RS-T45-4W	RS-ST58-4W	RS-ST64-2W	RS-ST64-4W	RS-ST64-6W
Picture	T Series  RS-T45-2W	T Series  RS-T45-4W	ST Series  RS-ST58-4W	ST Series  RS-ST64-2W	ST Series  RS-ST64-4W	ST Series  RS-ST64-6W
Voltage(V)	110V-130V 220V-240V	110V-130V 220V-240V	110V-130V 220V-240V	110V-130V 220V-240V	110V-130V 220V-240V	110V-130V 220V-240V
Wattage(W)	2W	4W	4W	2W	4W	6W
Lumen(lm)	220	440	440	220	440	660
Base	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15
Average Life (hrs.)	30000	30000	30000	30000	30000	30000
CCT	2700k/6000k	2700k/6000k	2700k/6000k	2700k/6000k	2700k/6000k	2700k/6000k
CRI (Ra)	90	90	90	90	90	90
Beam Angle	345°	345°	345°	345°	345°	345°
Model	RS-T30-185-6W	RS-T30-300-8W	RS-D60	More models available to customize:		Dimmable and shatterproof is available upon request
Picture	T Series  RS-T30-185-6W	T Series  RS-T30-300-8W	D Series  RS-D60-4W	  		
Voltage(V)	110V-130V 220V-240V	110V-130V 220V-240V	110V-130V 220V-240V	 		
Wattage(W)	2W	4W	4W			
Lumen(lm)	220	440	440			
Base	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15	E14/E12/E27/E26/ B22/B15			
Average Life (hrs.)	30000	30000	30000			
CCT	2700k/6000k	2700k/6000k	2700k/6000k			
CRI (Ra)	90	90	90			
Beam Angle	345°	345°	345°			