


**A5-R
5 inch Remodel Non-IC Recessed Housing**

Catalog #		Prepared by	
Project		Date	
Notes			



5 inch Remodel Non-IC Recessed Housing

Housing

- 1) Die-formed aluminum for maximum heat dissipation and rust protection
- 2) Designed for Remodel installation
- 3) Housing can be installed in 1/2" to 1-3/8" thick ceilings.
- 4) Housing is Non-IC rated must be kept at least 3" away from insulation

Junction Box

- 1) ETL listed for through branch wiring
- 2) 4 in-4 out J-box
- 3) Designed for straight through conduit runs
- 4) 1/2" and 3/4" romex wiring knockouts

Lamp

See trim for max. wattage and lamp
 CRI>80%
 PF>0.9
 Color Temperature:2700K-6500K

Listing

ETL listed for damp location W/Feed through

Order Matrix

A B C D E

Item No.:A5-R				
----------------------	--	--	--	--

A	Series
A5-R	5"/ Remodel NON-IC Housing

B	Input Voltage
120V	
277	277V

C	Lamp
P30	PAR30
R30	R30
A19	A19

D	Wattage
L12	LED 12W
L18	LED 18W

RECESSED DOWNLIGHT



Other Special requirement please confirm with factory

E	Color Temperature
28K	2800k
35K	3500K
50K	5000K
60K	6000K

RECESSED DOWNLIGHT



5" TRIM OPTICS



B5001
5" Baffle Trim
Lamp: R30/PAR30 LED E26 18W Max.



B5002
5" Reflector Trim
Lamp: R30/PAR30 LED E26 18W Max.



B5003
5" Eyeball Trim
Lamp: R30/PAR30 LED E26 18W Max.



B5003L
5" Large Eyeball Trim
Lamp: R30/PAR30 LED E26 18W Max.



B5007
5" Gimbal Ring Trim
Lamp: R30/PAR30 LED E26 18W Max.



B5011
5" Cone Baffle Trim
Lamp: A19 LED E26 12W Max.



B5011K
5" Baffle Trim
Lamp: R30/PAR30 LED E26 18W Max.



B5021
5" Clear Reflector Trim with Baffle
Lamp: A19 LED E26 12W Max.



B5022
5" Cone Reflector Trim
Lamp: A19 LED E26 12W Max.



B5300
5" Shower Trim with Fresnel Lens
Lamp: A19 LED E26 12W Max.
 Gasket used to prevent moisture
 Wet location listed

RECESSED DOWNLIGHT





B5400

5" Shower Trim with Albalite lens

Lamp: A19 LED E26 12W Max.

Gasket used to prevent moisture

Wet location listed



B5500

5" Shower Trim with Drop Opal

Lamp: A19 LED E26 12W Max.

Gasket used to prevent moisture

Wet location listed



B5602

5" Shower Trim with Dome Lens

Lamp: A19 LED E26 12W Max.

Gasket used to prevent moisture

Wet location listed



B5700

5" Shower Trim with Centre Frosted Lens

Lamp: A19 LED E26 12W Max.

Gasket used to prevent moisture

Wet location listed



B5800

5" Shower Trim with Frosted Lens

Lamp: A19 LED E26 12W Max.

Gasket used to prevent moisture

Wet location listed

RECESSED DOWNLIGHT

