



Square led multiple 4 lights supplier



Description

Easy Installation and maintenance

All parts and components accessible from below the ceiling

Lamp holders are adjustable 360° horizontal and 30° vertical for spot lighting in multiple directions

Actual adjustment may vary depending on the lamp beam spread

Housing

The inner trim is constructed of 22GA steel

Finish can be black, white or silver

Special finish please confirm with factory

Internal wire bundles are locked and covered with a glass sleeve

Junction box can be accessible from below the ceiling with a plate

Mounting Frame

Can accommodate a 1/2" to 1 1/4" ceiling thickness

Channel bracket allows up to 5" vertical adjustable

Universal mounting brackets included

Compatible with C-channel, flat bar, and EMT

C-channel are recommended for T-bar ceilings

Bar hangers must be ordered separately

Flanged Trim

Extruded trim frame includes torsion springs for convenient installations or removal from the housing





Accent Design Concepts

Item No.: MS4001

Trimless

Optional mud frame available for trimless mounting

The perforated mesh frame provided adheres to joint compound for seamless and trimless mounting

1. LED Light Engine

2800-6000k

CRI>80%

LED mounted to die-cast/extruded aluminum heat sink

50000 hours average rated life at 70% lumen

Electrical System

120-277V input

Class 2 power supply

Over voltage, over current and short circuit protection

Auto recovery

10% dimmable is available 120V only

10/15/17.8/20W each lamp

LM from 650-950 each lamp

2. Metal Halide Lamp Optics

T4 GU6.5 20/39W each lamp

Socket: GU6.5

Integral electronic ballast with 120-277V input

Ballast is accessible through ceiling opening via access door on housing wall

CDM-Tm PGJ5 20/39W each lamp

Socket: PGJ5

Ballast is accessible through ceiling opening via access door on housing wall

T6 G12 20/39/70W each lamp

Socket: G12

Ballast is accessible through ceiling opening via access door on housing wall

T4.5 G8.5 20/39/70W each lamp

Socket: G8.5

Ballast is accessible through ceiling opening via access door on housing wall

CMH MR16MH 20/39W



Accent Design Concepts, LLC.

Orlando, Florida 32824

Email: Sales@accentdesignconcepts.com

Website: www.accentdesignconcepts.com

Specifications subject to change w/o notice



Accent Design Concepts

Item No.: MS4001

Socket: GX10

Ballast is accessible through ceiling opening via access door on housing wall

PAR20MH 20/39W each lamp

Socket: E26

Ballast is accessible through ceiling opening via access door on housing wall

PAR30MH 39/70W each lamp

Socket: E26

Ballast is accessible through ceiling opening via access door on housing wall

Cross louvers and filters /MR16 cross louver, snoot and filters available and filters available

Must order separately

3. Other(Incandescent & LED)

MR16 12V 50W max each lamp

Socket: GU5.3

Ballast is accessible through ceiling opening via access door on housing wall

PAR20 50W max each lamp

Socket: E26

Ballast is accessible through ceiling opening via access door on housing wall

Long neck PAR30 75W max each lamp

Socket: E26

Ballast is accessible through ceiling opening via access door on housing wall

OSRAM AR111 each lamp

LED 20W each lamp

>80lm/w

Ballast is accessible through ceiling opening via access door on housing wall

Cross louvers and filters /MR16 cross louver, snoot and filters available

Must order separately



Accent Design Concepts, LLC.

Orlando, Florida 32824

Email: Sales@accentdesignconcepts.com

Website: www.accentdesignconcepts.com

Specifications subject to change w/o notice